



KwikWire™ Clamps

Part No.	For Use With Wire Rope Diameters	Box Qty.
BKC100	1/16" & 3/32"	100
BKC200	1/8" & 3/16"	50

See table below for KwikWire™ Clamp Working Loads

KwikWire™ Clamp Working Loads*

Clamp Part No.	Wire Rope Dia.	Lbs. Safety Factor 5
BKC100	1/16"	0-75
BKC100	3/32"	25-150
BKC200	1/8"	25-250
BKC200	3/16"	50-640

*Working loads shown are for hanging vertically.

For suspending at 15°, 30°, 45° or 60° angles from vertical, use the following percentage of the working loads from the chart:

15° = 96%
30° = 86%
45° = 70%
60° = 50%



KwikWire™ Wire Rope (Uncoated Galvanized Wire)

Part No.	Rope Dia.		Working Load		Spool
	in.	mm	Lbs.	kg	
BKW063 ⁽¹⁾	1/16"	(1.6)	96	(43.5)	500 ft.
BKW094 ⁽¹⁾	3/32"	(2.3)	184	(83.4)	500 ft.
BKW125 ⁽¹⁾	1/8"	(3.2)	340	(154.2)	500 ft.
BKW188 ⁽²⁾	3/16"	(4.8)	840	(381.0)	250 ft.

(1) Wire Rope Construction Type 7 x 7
(2) Wire Rope Construction Type 7 x 19

Instructions for installing the wire rope in the clamp - No tools are required.




1 Pass the wire rope through the KwikWire™ Clamp




2 Loop wire rope through/around support



3 Pass wire rope back through KwikWire™ Clamp



4 Push wire rope through clamp leaving 2" to 3" tail, then apply tension on wire rope



5 To adjust, remove tension and pull wire rope slightly to disengage teeth, slide adjustment pin in direction shown by arrow to release wire rope.



KwikPak™ Wire Rope & Clamps KwikPak

Part No.	For Use With Wire Rope Diameters	Box Qty.
BKP10063	BKC100 (100 pcs.) 1/16"Ø Wire Rope (500 ft.)	1
BKP10094	BKC100 (100 pcs.) 3/32"Ø Wire Rope (500 ft.)	1
BKP20125	BKC200 (50 pcs.) 1/8"Ø Wire Rope (500 ft.)	1
BKP20188	BKC200 (50 pcs.) 3/16"Ø Wire Rope (250 ft.)	1

KwikPak™ makes handling KwikWire™ a breeze!

- KwikPaks include KwikWire clamps and a spool of wire rope.
- KwikPaks are shipped in a specially designed dispenser box to ease field cutting of wire.

KwikWire™ System Recommendations:

- Do not exceed the safe working load of the products
- KwikWire™ Clamp load ratings are guaranteed only when used in combination with Cooper supplied wire rope
- Do not use for overhead lifting or hoisting
- Do not use if cable or components are visibly distorted or worn. Remove damaged cable end prior to inserting in KwikWire™ Clamp
- Do not paint cable near working area of KwikWire™ Clamp
- Do not apply lubricant
- Keep product clean and free of dirt
- Do not use clamp on coated wire rope
- Do not use in chlorinated or caustic atmospheres
- For use in dry locations
- Cooper's BKCC tool is recommended for cutting wire rope to prevent fraying



KwikWire™ Cable Cutter

Part No.	Box Qty.
BKCC	1

- Wire rope cutter for cutting all wire rope sizes

** Danger: Never use cutters on energized circuits, wire, or cable.



- KwikWire hanger combines the versatility of a bolt with an adjustable wire rope solution.
- Can be quickly installed in existing anchors or metal brackets with a nut.
- ARS, ARC, and ARW anchors are ideal for use with KwikWire Hangers.
- Ideal for supporting light fixtures, wire basket cable tray, HVAC ducts, and sign/banner supports.
- Allows for tool-less adjustment of wire rope.



Part No.	Thread Size	Wire Rope Dia.		Loading* SF5	
		in.	mm	Lbs.	kg
BKF100-4	1/4"-20	1/16"	(1.6)	45	(20.4)
		3/32"	(2.3)	90	(40.8)
BKF100-6	3/8"-16	1/16"	(1.6)	45	(20.4)
		3/32"	(2.3)	90	(40.8)

KwikWire™ Hanger installation




1
Screw KwikWire Hanger into installed hanger support (ARS anchor pictured)




2
Push cable wire up through the bottom of KwikWire Hanger




3
Continue pushing through until 1/4" minimum is extending out the side of the KwikWire Hanger



4
To adjust up - pull or push more cable wire through KwikWire Hanger



5
To adjust down - push up on bottom of KwikWire Hanger and allow cable wire to feed down



6
When hanging the cable wire is complete, cut off any excess cable wire if desired

KwikWire Accessory Features

- Reduces on the job installation time
- Can be installed quickly without drilling into existing structure
- Increases versatility in the field
- KwikWire accessory system reduces inventory and shipping costs
- No more sawing, filing, or fixing nuts
- Designed for use with cable tray, lighting, and HVAC
- Eliminates the need for all threaded rod
- Cost effective solution for jack chain
- “Y” style accessories require 50% less drilling



KwikWire Accessory Numbering System

Product Line	Assembly Configuration	Leg Termination	Leg Length	Wire Rope Diameter	Straight Length	Assembly or Kit
BK = KwikWire	Blank = Single Leg Y = 2 Legs 3 = 3 Legs	A = Angle Bracket w/Pin H = Hook L = Loop T = Toggle W = Fuse Cut B25 = Bolt w/ 1/4"-20 Thread B38 = Bolt w/ 3/8"-16 Thread BM6 = Bolt w/ M6 Thread BM8 = Bolt w/ M8 Thread BM10 = Bolt w/ M10 Thread	Blank = See Straight Length 18 = 18" Leg 30 = 30" Leg	063 = 1/16" 094 = 3/32"	Blank = Loop w/ Plastic Tube 18 = 18" 30 = 30" 40 = 40" 80 = 80" 120 = 120" 180 = 180" 240 = 240" 360 = 360"	Blank = Assembly Only K = Kit (Assembly & BKC100 Clamp)

Examples

BKYT18-094-120K

BK **Y** **T** **18** - **094** - **120** **K**

Cooper B-Line KwikWire Accessory

2 legs - toggle leg termination - 18" legs - 3/32" diameter wire - 120" straight length - kit with clamp

BKL-063-120K

BK **L** - **063** - **120** **K**

Cooper B-Line KwikWire Accessory

single leg - looped leg termination - 1/16" diameter wire - 120" straight length - kit with clamp

*Custom assemblies are available as shown by the red dot ● on pages 63 - 70.
Lead time on custom assemblies is 2 to 3 weeks depending on quantities.*

KwikWire™ Loop Termination

Part No.	Wire Rope Dia.		Length	
	in.	mm	in.	mm
● BKL-063-40	1/16"	(1.6)	40"	(1016)
● BKL-063-80	1/16"	(1.6)	80"	(2032)
● BKL-063-120	1/16"	(1.6)	120"	(3048)
● BKL-063-180	1/16"	(1.6)	180"	(4572)
● BKL-063-240	1/16"	(1.6)	240"	(6096)
● BKL-063-360	1/16"	(1.6)	360"	(9144)
● BKL-094-40	3/32"	(2.3)	40"	(1016)
● BKL-094-80	3/32"	(2.3)	80"	(2032)
● BKL-094-120	3/32"	(2.3)	120"	(3048)
● BKL-094-180	3/32"	(2.3)	180"	(4572)
● BKL-094-240	3/32"	(2.3)	240"	(6096)
● BKL-094-360	3/32"	(2.3)	360"	(9144)



Box Quantity - 20
5 bags containing 4 pieces per bag

KwikWire™ Loop Termination Kits

Part No.	Wire Rope Dia.		Length	
	in.	mm	in.	mm
● BKL-063-40K	1/16"	(1.6)	40"	(1016)
● BKL-063-80K	1/16"	(1.6)	80"	(2032)
● BKL-063-120K	1/16"	(1.6)	120"	(3048)
● BKL-063-180K	1/16"	(1.6)	180"	(4572)
● BKL-063-240K	1/16"	(1.6)	240"	(6096)
● BKL-063-360K	1/16"	(1.6)	360"	(9144)
● BKL-094-40K	3/32"	(2.3)	40"	(1016)
● BKL-094-80K	3/32"	(2.3)	80"	(2032)
● BKL-094-120K	3/32"	(2.3)	120"	(3048)
● BKL-094-180K	3/32"	(2.3)	180"	(4572)
● BKL-094-240K	3/32"	(2.3)	240"	(6096)
● BKL-094-360K	3/32"	(2.3)	360"	(9144)



Box Quantity - 20
5 bags containing 4 pieces per bag

Channel Nuts & Hardware

- Available as a wire rope with loop termination only or as a ready-to-use kit with a BKC100 clamp.
- Available in lengths of 40", 80", 120", 180", 240", and 360".

● = Stock item, lead time 2 - 3 working days ● = Non-stock item, lead time 10 - 15 working days

Single Style Hook Termination



Box Quantity - 20
5 bags containing 4 pieces per bag

Part No.	Wire Rope Dia.		Length	
	in.	mm	in.	mm
● BKH-094-40	3/32"	(2.3)	40"	(1016)
● BKH-094-80	3/32"	(2.3)	80"	(2032)
● BKH-094-120	3/32"	(2.3)	120"	(3048)
● BKH-094-180	3/32"	(2.3)	180"	(4572)
● BKH-094-240	3/32"	(2.3)	240"	(6096)
● BKH-094-360	3/32"	(2.3)	360"	(9144)


Single Style Hook Termination Kits



Box Quantity - 20
5 bags containing 4 pieces per bag

Part No.	Wire Rope Dia.		Length	
	in.	mm	in.	mm
● BKH-094-40K	3/32"	(2.3)	40"	(1016)
● BKH-094-80K	3/32"	(2.3)	80"	(2032)
● BKH-094-120K	3/32"	(2.3)	120"	(3048)
● BKH-094-180K	3/32"	(2.3)	180"	(4572)
● BKH-094-240K	3/32"	(2.3)	240"	(6096)
● BKH-094-360K	3/32"	(2.3)	360"	(9144)


'Y' Style Hook Termination With Loop



Box Quantity - 10
5 bags containing 2 pieces per bag

Part No.	Wire Rope Dia.		Length	
	in.	mm	in.	mm
● BKYH18-094	3/32"	(2.3)	18"	(457)
● BKYH30-094	3/32"	(2.3)	30"	(762)

- Hook designed to accept up to 3/8" diameter wire.
- Available as a wire rope with hook termination only or as a ready-to-use kit with a BKC100 clamp.
- Available in lengths of 40", 80", 120", 180", 240", and 360".
- Available in single, double (Y), and triple (3) leg styles



● = Stock item, lead time 2 - 3 working days ● = Non-stock item, lead time 10 - 15 working days

KwikWire™ 'Y' Style Hook Termination

Part No.	Leg Length		Wire Rope Dia.		Length	
	in.	mm	in.	mm	in.	mm
● BKYH18-094-40	18"	(457)	3/32"	(2.3)	40"	(1016)
● BKYH18-094-80	18"	(457)	3/32"	(2.3)	80"	(2032)
● BKYH18-094-120	18"	(457)	3/32"	(2.3)	120"	(3048)
● BKYH18-094-180	18"	(457)	3/32"	(2.3)	180"	(4572)
● BKYH18-094-240	18"	(457)	3/32"	(2.3)	240"	(6096)
● BKYH18-094-360	18"	(457)	3/32"	(2.3)	360"	(9144)
● BKYH30-094-40	30"	(762)	3/32"	(2.3)	40"	(1016)
● BKYH30-094-80	30"	(762)	3/32"	(2.3)	80"	(2032)
● BKYH30-094-120	30"	(762)	3/32"	(2.3)	120"	(3048)
● BKYH30-094-180	30"	(762)	3/32"	(2.3)	180"	(4572)
● BKYH30-094-240	30"	(762)	3/32"	(2.3)	240"	(6096)
● BKYH30-094-360	30"	(762)	3/32"	(2.3)	360"	(9144)



Box Quantity - 10
5 bags containing 2 pieces per bag

KwikWire™ 'Y' Style Hook Termination Kits

Part No.	Leg Length		Wire Rope Dia.		Length	
	in.	mm	in.	mm	in.	mm
● BKYH18-094-40K	18"	(457)	3/32"	(2.3)	40"	(1016)
● BKYH18-094-80K	18"	(457)	3/32"	(2.3)	80"	(2032)
● BKYH18-094-120K	18"	(457)	3/32"	(2.3)	120"	(3048)
● BKYH18-094-180K	18"	(457)	3/32"	(2.3)	180"	(4572)
● BKYH18-094-240K	18"	(457)	3/32"	(2.3)	240"	(6096)
● BKYH18-094-360K	18"	(457)	3/32"	(2.3)	360"	(9144)
● BKYH30-094-40K	30"	(762)	3/32"	(2.3)	40"	(1016)
● BKYH30-094-80K	30"	(762)	3/32"	(2.3)	80"	(2032)
● BKYH30-094-120K	30"	(762)	3/32"	(2.3)	120"	(3048)
● BKYH30-094-180K	30"	(762)	3/32"	(2.3)	180"	(4572)
● BKYH30-094-240K	30"	(762)	3/32"	(2.3)	240"	(6096)
● BKYH30-094-360K	30"	(762)	3/32"	(2.3)	360"	(9144)



Box Quantity - 10
5 bags containing 2 pieces per bag

Channel Nuts & Hardware

- Hook designed to accept up to 3/8" diameter wire.
- Available as a wire rope with loop termination only or as a ready-to-use kit with a BKC100 clamp.
- Available in lengths of 40", 80", 120", 180", 240", and 360".

● = Stock item, lead time 2 - 3 working days

● = Non-stock item, lead time 10 - 15 working days

KwikWire™ Single Style Toggle Termination



Box Quantity - 20
5 bags containing 4 pieces per bag

Part No.	Wire Rope Dia.		Length	
	in.	mm	in.	mm
● BKT-063-40	1/16"	(1.6)	40"	(1016)
● BKT-063-80	1/16"	(1.6)	80"	(2032)
● BKT-063-120	1/16"	(1.6)	120"	(3048)
● BKT-063-180	1/16"	(1.6)	180"	(4572)
● BKT-063-240	1/16"	(1.6)	240"	(6096)
● BKT-063-360	1/16"	(1.6)	360"	(9144)


KwikWire™ Single Style Toggle Termination Kits



Box Quantity - 20
5 bags containing 4 pieces per bag

Part No.	Wire Rope Dia.		Length	
	in.	mm	in.	mm
● BKT-063-40K	1/16"	(1.6)	40"	(1016)
● BKT-063-80K	1/16"	(1.6)	80"	(2032)
● BKT-063-120K	1/16"	(1.6)	120"	(3048)
● BKT-063-180K	1/16"	(1.6)	180"	(4572)
● BKT-063-240K	1/16"	(1.6)	240"	(6096)
● BKT-063-360K	1/16"	(1.6)	360"	(9144)


KwikWire™ 'Y' Style Toggle Termination With Loop



Box Quantity - 10
5 bags containing 2 pieces per bag

Part No.	Wire Rope Dia.		Length	
	in.	mm	in.	mm
● BKYT12-063	1/16"	(1.6)	12"	(305)
● BKYT18-063	1/16"	(1.6)	18"	(457)
● BKYT30-063	1/16"	(1.6)	30"	(762)

- Available as a wire rope with toggle termination only or as a ready-to-use kit with a BKC100 clamp.
- Available in lengths of 40", 80", 120", 180", 240", and 360".
- Available in single, double (Y), and triple (3) leg styles
- All triple (3) leg styles are non-stock, consult Cooper B-Line for lead times



● = Stock item, lead time 2 - 3 working days ● = Non-stock item, lead time 10 - 15 working days

KwikWire™ 'Y' Style Toggle Termination


Part No.	Leg Length		Wire Rope Dia.		Length	
	in.	mm	in.	mm	in.	mm
● BKYT12-063-40	12"	(305)	1/16"	(1.6)	40"	(1016)
● BKYT12-063-80	12"	(305)	1/16"	(1.6)	80"	(2032)
● BKYT12-063-120	12"	(305)	1/16"	(1.6)	120"	(3048)
● BKYT12-063-180	12"	(305)	1/16"	(1.6)	180"	(4572)
● BKYT12-063-240	12"	(305)	1/16"	(1.6)	240"	(6096)
● BKYT12-063-360	12"	(305)	1/16"	(1.6)	360"	(9144)
● BKYT18-063-40	18"	(457)	1/16"	(1.6)	40"	(1016)
● BKYT18-063-80	18"	(457)	1/16"	(1.6)	80"	(2032)
● BKYT18-063-120	18"	(457)	1/16"	(1.6)	120"	(3048)
● BKYT18-063-180	18"	(457)	1/16"	(1.6)	180"	(4572)
● BKYT18-063-240	18"	(457)	1/16"	(1.6)	240"	(6096)
● BKYT18-063-360	18"	(457)	1/16"	(1.6)	360"	(9144)
● BKYT30-063-40	30"	(762)	1/16"	(1.6)	40"	(1016)
● BKYT30-063-80	30"	(762)	1/16"	(1.6)	80"	(2032)
● BKYT30-063-120	30"	(762)	1/16"	(1.6)	120"	(3048)
● BKYT30-063-180	30"	(762)	1/16"	(1.6)	180"	(4572)
● BKYT30-063-240	30"	(762)	1/16"	(1.6)	240"	(6096)
● BKYT30-063-360	30"	(762)	1/16"	(1.6)	360"	(9144)



Box Quantity - 10
5 bags containing 2 pieces per bag

KwikWire™ 'Y' Style Toggle Termination Kits

Part No.	Leg Length		Wire Rope Dia.		Length	
	in.	mm	in.	mm	in.	mm
● BKYT12-063-40K	12"	(305)	1/16"	(1.6)	40"	(1016)
● BKYT12-063-80K	12"	(305)	1/16"	(1.6)	80"	(2032)
● BKYT12-063-120K	12"	(305)	1/16"	(1.6)	120"	(3048)
● BKYT12-063-180K	12"	(305)	1/16"	(1.6)	180"	(4572)
● BKYT12-063-240K	12"	(305)	1/16"	(1.6)	240"	(6096)
● BKYT12-063-360K	12"	(305)	1/16"	(1.6)	360"	(9144)
● BKYT18-063-40K	18"	(457)	1/16"	(1.6)	40"	(1016)
● BKYT18-063-80K	18"	(457)	1/16"	(1.6)	80"	(2032)
● BKYT18-063-120K	18"	(457)	1/16"	(1.6)	120"	(3048)
● BKYT18-063-180K	18"	(457)	1/16"	(1.6)	180"	(4572)
● BKYT18-063-240K	18"	(457)	1/16"	(1.6)	240"	(6096)
● BKYT18-063-360K	18"	(457)	1/16"	(1.6)	360"	(9144)
● BKYT30-063-40K	30"	(762)	1/16"	(1.6)	40"	(1016)
● BKYT30-063-80K	30"	(762)	1/16"	(1.6)	80"	(2032)
● BKYT30-063-120K	30"	(762)	1/16"	(1.6)	120"	(3048)
● BKYT30-063-180K	30"	(762)	1/16"	(1.6)	180"	(4572)
● BKYT30-063-240K	30"	(762)	1/16"	(1.6)	240"	(6096)
● BKYT30-063-360K	30"	(762)	1/16"	(1.6)	360"	(9144)



Box Quantity - 10
5 bags containing 2 pieces per bag

Channel Nuts & Hardware

- Available as a wire rope with loop termination only or as a ready-to-use kit with a BKC100 clamp.
- Available in lengths of 40", 80", 120", 180", 240", and 360".

● = Stock item, lead time 2 - 3 working days

● = Non-stock item, lead time 10 - 15 working days


KwikWire™ Bolt Termination



Box Quantity - 20
5 bags containing 4 pieces per bag

Part No.	Thread Size	Wire Rope Dia.		Length	
		in.	mm	in.	mm
● BKB25-063-40	1/4"-20	1/16"	(1.6)	40"	(1016)
● BKB25-063-80	1/4"-20	1/16"	(1.6)	80"	(2032)
● BKB25-063-120	1/4"-20	1/16"	(1.6)	120"	(3048)
● BKB25-063-180	1/4"-20	1/16"	(1.6)	180"	(4572)
● BKB25-063-240	1/4"-20	1/16"	(1.6)	240"	(6096)
● BKB25-063-360	1/4"-20	1/16"	(1.6)	360"	(9144)
● BKB38-094-40	3/8"-16	3/32"	(2.3)	40"	(1016)
● BKB38-094-80	3/8"-16	3/32"	(2.3)	80"	(2032)
● BKB38-094-120	3/8"-16	3/32"	(2.3)	120"	(3048)
● BKB38-094-180	3/8"-16	3/32"	(2.3)	180"	(4572)
● BKB38-094-240	3/8"-16	3/32"	(2.3)	240"	(6096)
● BKB38-094-360	3/8"-16	3/32"	(2.3)	360"	(9144)

- Ideal for use with ARS, ARC, ADI, ACPW, or ACPD anchors.
- Available as a wire rope with bolt termination only or as a ready-to-use kit with a BKC100 clamp.
- Available in lengths of 40", 80", 120", 180", 240", and 360".
- Available in single, double (Y), and triple leg (3) styles
- All (Y) and triple (3) styles are non-stock, consult Cooper B-Line for lead times



● = Stock item, lead time 2 - 3 working days ● = Non-stock item, lead time 10 - 15 working days



KwikWire™ Bolt Termination Kits

Part No.	Thread Size	Wire Rope Dia.		Length	
		in.	mm	in.	mm
● BKB25-063-40K	1/4"-20	1/16"	(1.6)	40"	(1016)
● BKB25-063-80K	1/4"-20	1/16"	(1.6)	80"	(2032)
● BKB25-063-120K	1/4"-20	1/16"	(1.6)	120"	(3048)
● BKB25-063-180K	1/4"-20	1/16"	(1.6)	180"	(4572)
● BKB25-063-240K	1/4"-20	1/16"	(1.6)	240"	(6096)
● BKB25-063-360K	1/4"-20	1/16"	(1.6)	360"	(9144)
● BKB38-094-40K	3/8"-16	3/32"	(2.3)	40"	(1016)
● BKB38-094-80K	3/8"-16	3/32"	(2.3)	80"	(2032)
● BKB38-094-120K	3/8"-16	3/32"	(2.3)	120"	(3048)
● BKB38-094-180K	3/8"-16	3/32"	(2.3)	180"	(4572)
● BKB38-094-240K	3/8"-16	3/32"	(2.3)	240"	(6096)
● BKB38-094-360K	3/8"-16	3/32"	(2.3)	360"	(9144)



Box Quantity - 20
5 bags containing 4 pieces per bag

- Ideal for use with ARS, ARC, ADI, ACPW, or ACPD anchors.
- Available as a wire rope with bolt termination only or as a ready-to-use kit with a BKC100 clamp.
- Available in lengths of 40", 80", 120", 180", 240", and 360".
- Available in single, double (Y), and triple (3) styles
- All double (Y) and triple (3) styles are non-stock, consult Cooper B-Line for lead times



Double (Y) leg style



Triple (3) leg style

● = Stock item, lead time 2 - 3 working days

● = Non-stock item, lead time 10 - 15 working days

KwikWire™ Angle Bracket Termination



Box Quantity - 20
5 bags containing 4 pieces per bag

Part No.	Wire Rope Dia.		Length	
	in.	mm	in.	mm
● BKA-063-40	1/16"	(1.6)	40"	(1016)
● BKA-063-80	1/16"	(1.6)	80"	(2032)
● BKA-063-120	1/16"	(1.6)	120"	(3048)
● BKA-063-180	1/16"	(1.6)	180"	(4572)
● BKA-063-240	1/16"	(1.6)	240"	(6096)
● BKA-063-360	1/16"	(1.6)	360"	(9144)

KwikWire™ Angle Bracket Termination Kits



Box Quantity - 20
5 bags containing 4 pieces per bag

Part No.	Wire Rope Dia.		Length	
	in.	mm	in.	mm
● BKA-063-40K	1/16"	(1.6)	40"	(1016)
● BKA-063-80K	1/16"	(1.6)	80"	(2032)
● BKA-063-120K	1/16"	(1.6)	120"	(3048)
● BKA-063-180K	1/16"	(1.6)	180"	(4572)
● BKA-063-240K	1/16"	(1.6)	240"	(6096)
● BKA-063-360K	1/16"	(1.6)	360"	(9144)

- Available as a wire rope with angle bracket termination only or as a ready-to-use kit with a BKC100 clamp.
- Available in lengths of 40", 80", 120", 180", 240", and 360".

● = Stock item, lead time 2 - 3 working days ● = Non-stock item, lead time 10 - 15 working days