

24 and WER Type



Specifications

Description: Flat, non-indicating visible link element mounted on 1 inch centers using either No. 6 or No. 10 screws.

Dimensions: See Dimensions illustration.

Ratings:

Volts: — 32Vdc ($\frac{1}{4}$, 1, 3 $\frac{1}{2}$, 8, 10A)

— 60Vdc ($\frac{1}{2}$, $\frac{3}{4}$, 1 $\frac{1}{2}$, 2, 3, 4, 5A)

Amps: — $\frac{1}{4}$ -10A

Agency Information: CE, UL Recognized File E56412.

Catalog Numbers

Catalog Numbers	Amp Rating	DC Volts	Color Code	Lucent Comcode Ref. No.	A Length Inches
WER- $\frac{1}{4}$	$\frac{1}{4}$	32	—	—	—
24E- $\frac{1}{2}$ *	$\frac{1}{2}$	60	Red	100202894	0.20
24D- $\frac{3}{4}$ *	$\frac{3}{4}$	60	Black	100202886	0.15
WER-1	1	32	—	—	—
24G-1- $\frac{1}{3}$ *	1 $\frac{1}{3}$	60	White	100202910	0.20
24C-2*	2	60	Orange	100202878	0.20
24B-3*	3	60	Blue	100202852	0.15
WER-3- $\frac{1}{2}$	3 $\frac{1}{2}$	32	—	—	—
24B-4*	4	60	Yellow	100202860	0.15
24F-5*	5	60	Green	100202902	0.15
WER-8	8	32	—	—	—
WER-10	10	32	—	—	—
64A-Dummy	—	—	—	100203280	—

*Designed to comply with Bellcore Technical Reference TR-TSY-000799 Issue 1, Dec. 1988.

Dimensions - in

