

**Architectural Products Group, LED Quick Ship Program 2017/2018**  
Ametrix - Corelite - Neo-Ray



**EATON**

*Powering Business Worldwide*

Eaton's Architectural Product Group offers a quick ship program focused on their most popular LED luminaires that cover a wide array of architectural lighting applications. The 10 day lead time on select products caters to fast moving construction projects and will ensure that the schedules are met and the project is a success.

### **Terms of Quick Ship Program:**

- 10 Day lead times
- 1000 linear feet maximum order for continuously mounted product (4', 8', and 12' sections only. See specific product families for more detail)
- 200 piece maximum order for recessed 2x2 and 2x4 luminaires, and LED Cove.

### **Notes:**

- All products must have a "QS-" at the beginning of the catalog number.
- No submittal sign-off required
- Custom color not available
- Standard freight terms apply
- Standard Terms and Conditions apply
- Cancellations or changes will not be accepted



### LC32

Cove  
1' and 2' Continuous Mounting

Sample Number: QS-LC-1-40K-1-ELV-UNV-24-00

Product	Light Level	Color Temperature	Number of Circuits	Wiring	Voltage	Module Size	Aiming
<b>QS-LC</b> = Quick Ship LED Cove	<b>1</b> = Light Level 1	<b>35K</b> = 3500K <b>40K</b> = 4000K	<b>1</b> = 1 Circuit	<b>ELV</b> = ELV Dimming	<b>UNV</b> = Universal (120V-277V)	<b>12</b> = 12" module length <b>24</b> = 24" module length	<b>00</b> = 0 degree tilt



### Divide Suspended

Suspended  
4', 8' and Continuous Mounting

CORELITE

Sample Number: QS-DSI-WS-3L35-LD2-1D-UNV-AC48-T1-16'-STD-W

Series	Optics	Light Level	Color Temperature	LED Version	Number of Circuits	Wiring	Voltage
<b>QS-DSI</b> = Divide Suspended Series, Quick Ship	<b>WS</b> = Wavestream	<b>1</b> = Light Level 1 <b>2</b> = Light Level 2 <b>3</b> = Light Level 3 <b>4</b> = Light Level 4 <b>5</b> = Light Level 5	<b>L35</b> = 3500K <b>L40</b> = 4000K	<b>LD2</b> = LED 2.0	<b>1</b> = 1 Circuit	<b>C</b> = Switched Circuit <b>D</b> = Dimming	<b>UNV</b> = Universal (120V-277V)
Suspension	Suspension Length	Ceiling Type	Run Length	Driver Options	Integral Control Options	Top Cover	Finish
<b>AC</b> = Aircraft cable with straight power cord	Adjustable Cable: <b>48</b> = 48" <b>120</b> = 120"	<b>T1</b> = 1" T-Bar <b>T9</b> = 9/16" T-Bar <b>TS</b> = Slotted T-Bar <b>ST</b> = Structure <b>JB</b> = 4" Octagonal J-Box	<b>4</b> = 4' <b>8</b> = 8' <b>XX</b> = Specify Row Length <sup>1</sup>	<b>STD</b> = Standard 0-10V Driver	N/A	N/A	<b>W</b> = White

Notes: 1. Standard row configurations over 8' are built with 4' and 8' luminaires.



### Jaylum LED

Suspended  
4', 8' and Continuous Mounting

CORELITE

Sample Number: QS-J2-WL-3L35-1D-UNV-AC48-T1-28'-STD-W

Series	Optics Up	Optics Down	Light Level	Color Temperature	Number of Circuits	Wiring	Voltage
<b>QS-J2</b> = Jaylum Suspended, Quick Ship	<b>W</b> = White	<b>L</b> = Frosted Lens	<b>1</b> = Light Level 1 <b>2</b> = Light Level 2 <b>3</b> = Light Level 3	<b>L35</b> = LED 3500K <b>L40</b> = LED 4000K	<b>1</b> = 1 Circuit	<b>C</b> = Switched Circuit <b>D</b> = Dimming	<b>UNV</b> = Universal (120V-277V)
Suspension/Power Feed	Suspension Length	Ceiling Type	Run Length	Driver Options	Integral Control Options	Top Cover	Finish
<b>AC</b> = Adjustable aircraft cable with straight power cord	Adjustable Cable: <b>48</b> = 48" <b>120</b> = 120"	<b>T1</b> = 1" T-Bar <b>T9</b> = 9/16" T-Bar <b>TS</b> = Slotted T-Bar <b>ST</b> = Structure <b>JB</b> = 4" Octagonal J-Box	<b>4</b> = 4' <b>8</b> = 8' <b>XX</b> = Specify Row Length <sup>1</sup>	<b>STD</b> = Standard 0-10V Driver	N/A	N/A	<b>W</b> = White

Notes: 1. Standard row configurations over 8' are built with 4' and 8' luminaires.



## RZL

CORELITE

Suspended  
4', 8', 12' and Continuous Mounting

Sample Number: QS-RZL-WB-3L35-1D-UNV-AC48-T1-28'-STD-W

Series	Optics Up	Optics Down	Light Level	Color Temperature	Number of Circuits	Wiring	Voltage
<b>QS-RZL</b> = RZL Linear Semi-direct LED Luminaire, Quick Ship	<b>W</b> = With Uplight	<b>L</b> = Frosted Lens <b>B</b> = Internal Micro Baffle with Clear Linear Prismatic Lens	<b>1</b> = Light Level 1 <b>2</b> = Light Level 2 <b>3</b> = Light Level 3 <b>4</b> = Light Level 4 <b>5</b> = Light Level 5	<b>L35</b> = LED 3500K <b>L40</b> = LED 4000K	<b>1</b> = 1 Circuit	<b>C</b> = Switched Circuit <b>D</b> = Dimming	<b>UNV</b> = Universal (120V-277V)
Suspension/Power Feed	Suspension Length	Ceiling Type	Run Length	Driver Options	Integral Control Options	Finish	
<b>AC</b> = Adjustable aircraft cable with straight power cord	Adjustable Cable: <b>48</b> = 48" <b>120</b> = 120"	<b>T1</b> = 1" T-Bar <b>T9</b> = 9/16" T-Bar <b>TS</b> = Slotted T-Bar <b>ST</b> = Structure <b>JB</b> = 4" Octagonal J-Box	<b>4</b> = 4' <b>8</b> = 8' <b>12</b> = 12' <b>XX</b> = Specify Row Length <sup>1</sup>	<b>STD</b> = Standard 0-10V Driver	N/A	<b>W</b> = White	

Notes: 1. Standard row configurations over 12' are built with 8' and 12' luminaires.



## RZL Surface

CORELITE

Ceiling Surface Mount  
4', 8', 12' and Continuous Mounting

Sample Number: QS-RZL-WB-3L35-1D-UNV-SU-JB-28'-STD-W

Series	Optics Up	Optics Down	Light Level	Color Temperature	Number of Circuits	Wiring	Voltage
<b>QS-RZL</b> = RZL Linear Semi-direct LED Luminaire, Quick Ship	<b>W</b> = With Uplight	<b>L</b> = Frosted Lens <b>B</b> = Clear Linear Prismatic Lens with Internal Micro Baffle	<b>1</b> = Light Level 1 <b>2</b> = Light Level 2 <b>3</b> = Light Level 3 <b>4</b> = Light Level 4 <b>5</b> = Light Level 5	<b>L35</b> = LED 3500K <b>L40</b> = LED 4000K	<b>1</b> = 1 Circuit	<b>C</b> = Switched Circuit <b>D</b> = Dimming	<b>UNV</b> = Universal (120V-277V)
Mounting	Run Length	Driver Options	Integral Control Options	Finish			
<b>SU-JB</b> = Surface Mount - Junction Box	<b>4</b> = 4' <b>8</b> = 8' <b>12</b> = 12' <b>XX</b> = Specify Row Length <sup>1</sup>	<b>STD</b> = Standard 0-10V Driver	N/A	<b>W</b> = White			

Notes: 1. Standard row configurations over 12' are built with 8' and 12' luminaires.



## Divide

CORELITE

Recessed  
2'x2' and 2'x4'

Sample Number: QS-DRI-WS-3L35-UNV-22-T1-STD

Series	Optics	Light Level	Color Temperature	Voltage	Size	Ceiling Type	Driver Options
<b>QS-DRI</b> = Divide Recessed Series, Quick Ship	<b>WS</b> = Wavestream	1 = Light Level 1 2 = Light Level 2 3 = Light Level 3 4 = Light Level 4 5 = Light Level 5 6 = Light Level 6 <sup>1</sup>	<b>L35</b> = LED 3500K <b>L40</b> = LED 4000K	<b>UNV</b> = Universal (120V-277V)	<b>22</b> = 2'x2' <b>24</b> = 2'x4'	<b>T1</b> = 1" Grid, Slot Grid, and 9/16" Tegular <b>T9</b> = 9/16" Grid <b>CC</b> = Concealed Ceiling	<b>STD</b> = Standard 0-10V Driver

Notes: 1. Light Level 6 not available in 2x4 size



## Class R2X LED

CORELITE

Recessed  
2'x2' and 2'x4'

Sample Number: QS-R2X-WO-3L35-LD5-UNV-22-T1-STD

Series	Shielding	Light Level	Color Temperature	LED Version	Voltage	Size	Ceiling Type	Driver Options
<b>QS-R2X</b> = Class R2X LED, Quick Ship	<b>WO</b> = Opal Lens	1 = Light Level 1 2 = Light Level 2 3 = Light Level 3 4 = Light Level 4 5 = Light Level 5 6 = Light Level 6	<b>L35</b> = LED 3500K <b>L40</b> = LED 4000K	<b>LD5</b> = LED 5.0	<b>UNV</b> = Universal (120V-277V)	<b>22</b> = 2'x2' <b>24</b> = 2'x4'	<b>T1</b> = 1" Grid, Slot Grid, and 9/16" Tegular <b>T9</b> = 9/16" Grid	<b>STD</b> = Standard 0-10V Driver



## Class R3/Z3 LED

CORELITE

Recessed  
2'x2' and 2'x4'

Sample Number: QS-R3-WL-2L35-LD5-UNV-22-T1-STD

Series	Shielding	Light Level	Color Temperature	LED Version	Voltage	Size	Ceiling Type	Driver Options
<b>QS-R3</b> = Class R3, Quick Ship <b>QS-Z3</b> = Class Z3, Quick Ship	<b>WL</b> = Linear Prismatic Lens	1 = Light Level 1 2 = Light Level 2 3 = Light Level 3 4 = Light Level 4 5 = Light Level 5 6 = Light Level 6 <sup>1</sup>	<b>L35</b> = LED 3500K <b>L40</b> = LED 4000K	<b>LD5</b> = LED 5.0	<b>UNV</b> = Universal (120V-277V)	<b>22</b> = 2'x2' <b>24</b> = 2'x4'	<b>T1</b> = 1" Grid, Slot Grid, and 9/16" Tegular <b>T9</b> = 9/16" Grid	<b>STD</b> = Standard 0-10V Driver

Notes: 1. Light Level 6 not available in 2x4 size



## Define 2

Recessed  
2" width

NEO-RAY

Sample Number: **QS-S122-DR-2-35-ETG-0048-1-U-DD-1-W**

Series	Light Distribution	Light Level	Color Temperature	Ceiling Type	Length	
<b>QS-S122</b> = Define 2 Quick Ship	<b>DR</b> = Direct Recessed	<b>L0</b> = Light Level 0 <b>1</b> = Light Level 1 <b>2</b> = Light Level 2	<b>30</b> = LED 3000K <b>35</b> = LED 3500K <b>40</b> = LED 4000K	<b>ETG</b> = 15/16" T-Grid <b>FTG</b> = 9/16" Grid <b>GYP</b> = Gypsum board	<b>0048</b> = 4' Individual <b>0096</b> = 8' Individual	
Circuiting	Voltage	LED Driver	Emergency Options	Options	Shielding	Color
<b>1</b> = Single Circuit	<b>UNV</b> = Universal (120V-277V)	<b>DD</b> = 0-10V dimming	N/A	N/A	<b>1</b> = Satin Flush Diffuser <b>4</b> = Satin Drop Diffuser	<b>W</b> = Matte White



## Define 3

Recessed  
3" width

NEO-RAY

Sample Number: **QS-S123-DR-2-35-ETG-0048-1-U-DD-1-W**

Series	Light Distribution	Light Level	Color Temperature	Ceiling Type	Length	
<b>QS-S123</b> = Define 3 Quick Ship	<b>DR</b> = Direct Recessed	<b>L0</b> = Light Level 0 <b>1</b> = Light Level 1 <b>2</b> = Light Level 2	<b>30</b> = LED 3000K <b>35</b> = LED 3500K <b>40</b> = LED 4000K	<b>ETG</b> = 15/16" T-Grid <b>FTG</b> = 9/16" Grid <b>GYP</b> = Gypsum board	<b>0048</b> = 4' Individual <b>0096</b> = 8' Individual	
Circuiting	Voltage	LED Driver	Emergency Options	Options	Shielding	Color
<b>1</b> = Single Circuit	<b>UNV</b> = Universal (120V-277V)	<b>DD</b> = 0-10V dimming	N/A	N/A	<b>1</b> = Satin Flush Diffuser <b>4</b> = Satin Drop Diffuser	<b>W</b> = Matte White



## Define 4

Recessed  
4" width

NEO-RAY

Sample Number: **QS-S122-DR-2-35-ETG-0048-1-U-DD-1-W**

Series	Light Distribution	Light Level	Color Temperature	Ceiling Type	Length	
<b>QS-S124</b> = Define 4 Quick Ship	<b>DR</b> = Direct Recessed	<b>L0</b> = Light Level 0 <b>1</b> = Light Level 1 <b>2</b> = Light Level 2	<b>30</b> = LED 3000K <b>35</b> = LED 3500K <b>40</b> = LED 4000K	<b>ETG</b> = 15/16" T-Grid <b>FTG</b> = 9/16" Grid <b>GYP</b> = Gypsum board	<b>0048</b> = 4' Individual <b>0096</b> = 8' Individual	
Circuiting	Voltage	LED Driver	Emergency Options	Options	Shielding	Color
<b>1</b> = Single Circuit	<b>UNV</b> = Universal (120V-277V)	<b>DD</b> = 0-10V dimming	N/A	N/A	<b>1</b> = Satin Flush Diffuser <b>4</b> = Satin Drop Diffuser	<b>W</b> = Matte White



## Define 5

Recessed  
5" width

NEO-RAY

Sample Number: **QS-S125-DR-2-35-ETG-0048-1-U-DD-1-W**

Series	Light Distribution	Light Level	Color Temperature	Ceiling Type	Length	
<b>QS-S123</b> = Define 5 Quick Ship	<b>DR</b> = Direct Recessed	<b>L0</b> = Light Level 0 <b>1</b> = Light Level 1 <b>2</b> = Light Level 2	<b>30</b> = LED 3000K <b>35</b> = LED 3500K <b>40</b> = LED 4000K	<b>ETG</b> = 15/16" T-Grid <b>FTG</b> = 9/16" Grid <b>GYP</b> = Gypsum board	<b>0048</b> = 4' Individual <b>0096</b> = 8' Individual	
Circuiting	Voltage	LED Driver	Emergency Options	Options	Shielding	Color
<b>1</b> = Single Circuit	<b>UNV</b> = Universal (120V-277V)	<b>DD</b> = 0-10V dimming	N/A	N/A	<b>1</b> = Satin Flush Diffuser <b>4</b> = Satin Drop Diffuser	<b>W</b> = Matte White

**Lighting Product Lines**

Halo  
Halo Commercial  
Portfolio  
Iris  
RSA  
Metalux  
Corelite  
Neo-Ray  
Fail-Safe  
MWS  
Ametrix  
Shaper  
io  
Lumark  
McGraw-Edison  
Invue  
Ephesus  
Lumière  
Streetworks  
AtLite  
Sure-Lites

**Controls Product Lines**

Greengate  
iLumin  
Zero 88  
Fifth Light Technology  
iLight (International Only)

**Connected Lighting Systems**

LumaWatt Pro  
WaveLinx  
Distributed Low-Voltage Power  
ConnectWorks



**Eaton**  
1121 Highway 74 South  
Peachtree City, GA 30269  
P: 770-486-4800  
[www.eaton.com/lighting](http://www.eaton.com/lighting)

Canada Sales  
5925 McLaughlin Road  
Mississauga, Ontario L5R 1B8  
P: 905-501-3000  
F: 905-501-3172

© 2017 Eaton  
All Rights Reserved  
Printed in USA  
Publication No. BR525081EN  
September 2017

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Product availability, specifications, and compliances are subject to change without notice.