

Eaton Lighting Solutions are Ready for Control

Metalux LED lighting fixtures are Powered by Fifth Light, starting with standard drivers that work with wall dimmers and sensors, up to digital drivers that work with Fifth Light whole-building systems. Together, Metalux and Eaton Lighting Systems will improve energy savings and user comfort for any space.

0 - 10V Dimming is standard

Metalux LED products include 0-10V (analog) dimming for direct control using Eaton wall dimmers, Greengate Room Controllers, sensors, and lighting control panels, as well as third-party devices. Consult the table below for a list of tested dimming products, and their dimming range.

0 - 10V 1% Dimming is available

For demanding applications, 1% dimming is optional for many lumen packages by specifying the HCD option. This option is available in select Metalux luminaires. Consult specification sheets for details.

Product Category	Part #	Description	Rating	-CD Dimming Range	-HCD Dimming Range
Dimmers	SF10P	Eaton Skye 0-10V Slide Dimmer	120/277VAC	10% - 100%	1% - 100%
	DF10P	Eaton Devine 0-10V Slide Dimmer	120/277VAC	10% - 100%	1% - 100%
	IP710	Leviton 0-10V Slide Dimmer	120/277VAC	15% - 100%	1% - 100%
	AWSMT-7DW	Leviton Renoir II 0-10V Slide Dimmer, Thin	120/277VAC	15% - 100%	1% - 100%
	AWSMG-7DW	Leviton Renoir II 0-10V Slide Dimmer	120/277VAC	15% - 100%	1% - 100%
	AMRMG-7DW	Leviton Renoir II 0-10V Rotary Dimmer	120/277VAC	15% - 100%	1% - 100%
	DVTV or DVSCTV	Lutron Diva 0-10V Dimmer	120/277VAC	10% - 100%	1% - 100%
	NFTV	Lutron Nova 0-10V Dimmer	120/277VAC	10% - 100%	1% - 100%
	NTFTV	Lutron NovaT 0-10V Dimmer, Thin	120/277VAC	10% - 100%	1% - 100%
Sensors	Eaton Lighting Systems: all Greengate Occupancy Sensors (120/277VAC) On/Off Eaton Lighting Systems: DLC-PD-DIM (daylight sensor) (0-10V) dimming range based on driver				
Lighting Control Panels	Eaton Lighting Systems RC3 Room Controller Series 10% - 100% (-CD Driver) 1% - 100% (HCD Driver) Eaton Lighting Systems: CK4A-* (0-10V dimming) 10% - 100% (-CD Driver) 1% - 100% (HCD Driver) Source Controllers (0-10V dimming) 10% - 100% (-CD Driver) 1% - 100% (HCD Driver)				

Fifth Light Digital Addressable Lighting Interface (DALI) Control Systems

Go Digital! Consult the Metalux LED product data sheet for availability of native DALI drivers for direct compatibility with the capable and scalable Fifth Light controllers and software. For details on the Fifth Light solution, please visit the website - [click here](#)



Eaton
1121 Highway 74 South
Peachtree City, GA 30269
P: 770-486-4800
www.eaton.com/lighting

Canada Sales
5925 McLaughlin Road
Mississauga, Ontario L5R 1B8
P: 905-501-3000
F: 905-501-3172

© 2016 Eaton
All Rights Reserved
Printed in USA
Publication No. WP519003EN
January 8, 2016

Eaton is a registered trademark.
All other trademarks are property of their respective owners.
Product availability, specifications, and compliances are subject to change without notice.