

**SELD**

Industrial LED emergency lighting

**Sure-Lites**



**Save  
Money**



**Save  
Time**



**Get  
Peace of Mind**

The SELD series is the most capable and code-compliant industrial LED emergency fixture in the market; specifying is as simple as picking a color.



white



silver



black



**EATON**

*Powering Business Worldwide*



# SELD Industrial LED emergency lighting



	Feature	Benefit	Result
<b>Performance</b>	Superior egress coverage; up to 60 feet	Less fixtures required	💰
	-30°C to 50°C temperature range	Design flexibility	☮
	Self-diagnostics with laser test	Reduced NFPA testing costs	💰
<b>Construction</b>	Industrial die cast aluminum/polycarbonate housing	Environment - proof	☮
	Two 330 Lumen LED sources; Nickel Cadmium battery	No maintenance	💰
	EZ hang installation	Reduced installation time	🕒
<b>Compliance</b>	NEMA 4X/IP66/NSF/UL924 wet location standard	Ease of specifying / ordering	🕒
	5-year product warranty; 7-year prorated battery warranty	No worries	☮
	Hazardous Class 1, Division 2 option	Design flexibility	🕒

## Ordering Information

Series	Housing	Wet Location	Egress Coverage	Color	Self Diagnostics	Hazardous Location
<b>SEL</b> = LED Emergency light	<b>D</b> = Die cast	<b>W</b> = Wet location (-30°C to 50°C)	<b>60</b> = 60 ft.	___ = silver <b>BK</b> = black <b>WH</b> = white	<b>SD</b> = Self Diagnostics (standard)	___ = not Hazardous <b>HAZ</b> = Hazardous



## Competitor Comparison

✓ = Market Leading

Feature	SELD	Competitor A	Competitor B	Competitor C	Competitor D
Housing Material	Die cast aluminum ✓	Polycarbonate	Thermoplastic	Die cast aluminum ✓	Die cast aluminum ✓
Source	Integrated LED ✓	NonLED	LED lamp	MR16 or LED lamp	MR16 or LED lamp
Egress Coverage	58' standard ✓	26' standard	58' standard ✓	Various	Up to 50'
Battery	Nickel Cadmium ✓	Lead Acid	Lithium Ion	Nickel Cadmium ✓	Nickel Metal Hydride
-30°C to 50°C Temp	Standard ✓	Option	Option	Option	Not available
NEMA 4X	Standard ✓	Standard ✓	Option	Standard ✓	Standard ✓
IP 66	Standard ✓	Standard ✓	Option	Not available	Not available
NSF	Standard ✓	Standard ✓	Option	Not available	Standard ✓
Self-Diagnostics	Standard ✓	Option	Option	Option	Option
Warranty	5-year ✓	3-year	3-year	3-year	3-year
Hazardous Option	Option ✓	Not available	Option ✓	Not available	Not available