



Complex environment locking devices

Product description


2-pole, 3-wire grounding
15A, 277V/AC
NEMA L7-15



24W34



65W34DPLX



CRL520P

Plugs & connectors

Rating A	V/AC	NEMA	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.		
15	277	L7-15	Watertight	0.30-0.65" (7.6-16.5mm)	Y	<input type="checkbox"/> 24W34	<input type="checkbox"/> 25W34		
			Watertight	0.30-0.65" (7.6-16.5mm)	BK	<input type="checkbox"/> 24W34BK	<input type="checkbox"/> 25W34BK		

Receptacles

Rating A	V/AC	NEMA	Description	Color	Single receptacle catalog no.	Duplex receptacle catalog no.		
15	277	L7-15	Watertight	Y	<input type="checkbox"/> 65W34	<input type="checkbox"/> 65W34DPLX		
			Watertight	BK	<input type="checkbox"/> 65W34BK	<input type="checkbox"/> 65W34DPLXBK		

Complex environment locking devices

Product description

2-pole, 3-wire grounding
20A, 125V/AC
NEMA L5-20



Plugs & connectors

Rating A	V/AC	NEMA	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.		
20	125	L5-20	Watertight	0.36-0.84" (9.1-21.3mm)	Y	<input type="checkbox"/> L520PW	<input type="checkbox"/> L520CW		
			Watertight	0.36-0.84" (9.1-21.3mm)	BK	<input type="checkbox"/> L520PWBK	<input type="checkbox"/> L520CWBK		
			Severe duty	0.38-1.00" (9.7-25.4mm)	Y & BK	<input type="checkbox"/> L520PY	<input type="checkbox"/> L520CY		
			Safety grip corrosion resistant	0.38-1.00" (9.7-25.4mm)	Y	<input type="checkbox"/> CRL520P	<input type="checkbox"/> CRL520C		

Receptacles

Rating A	V/AC	NEMA	Description	Color	Single receptacle catalog no.		
20	125	L5-20	Watertight	Y	<input type="checkbox"/> L520RW ^{A*}		
			Watertight	BK	<input type="checkbox"/> L520RWBK ^{A*}		
			Corrosion resistant	Y	<input type="checkbox"/> CRL520R		


*Not Fed Spec, ^A cULus Listed

Dimensional information:
D-34-35

Specification information:
Watertight industrial plugs & connectors: D-38
Watertight industrial receptacles: D-39
Severe duty industrial plugs & connectors: D-40
Corrosion resistant: D-41

Color information:

BK (Black), Y (Yellow)



Compliances, specifications and availability are subject to change without notice.

Indicates NAFTA compliant - Page Q-32

RoHS compliant - Page Q-32