

Temporary Power Centers

Project Name:	Prepared By:
Project Number:	Date:
Catalog Number:	Type:



Temporary Power Centers with GFCI Protection

50A
120/240 VAC



RB300M

Temporary Power Centers

FEATURES

- Safely centralize and distribute or hub and spoke temporary power.
- Unique patented “stackable” design allows multiple RhinoBox units to lock together for safe transport and storage.
- Available in NEMA 3R Rainproof and NEMA 1 enclosures.
- Weatherproof receptacle covers and flip-up circuit breaker cover prevent nuisance tripping and protect from damage and weather.

RhinoBox™ NEMA 3R



A	VAC	Distribution Devices	Receptacle Ratings	Receptacle Compon.	Protection Overload	GFCI	Catalog No.
50	120/240 (Max.)	(6) WR Duplex Receptacles	20A, 125V	WRBR20BK	✓	✓	<input type="checkbox"/> RB300M
		(1) Locking Receptacle	30A, 250V	L630R	✓	-	
		(1) Locking Inlet	50A, 125/250V	CS6375RB	-	-	
		(1) Locking Outlet	50A, 125/250V	CS6369RB	-	-	
50	120/240 (Max.)	(6) Single Receptacles	20A, 125V	1877BK	✓	✓	<input type="checkbox"/> RB301M
		(1) Locking Receptacle	30A, 250V	L630R	✓	-	
		(1) Locking Inlet	50A, 125/250V	CS6375RB	-	-	
		(1) Locking Outlet	50A, 125/250V	CS6369RB	-	-	
50	120/240 (Max.)	(6) Locking Receptacles	20A, 125V	L520R	✓	✓	<input type="checkbox"/> RB302M
		(1) Locking Receptacle	30A, 250V	L630R	✓	-	
		(1) Locking Inlet	50A, 125/250V	CS6375RB	-	-	
		(1) Locking Outlet	50A, 125/250V	CS6369RB	-	-	
50	120/240 (Max.)	(3) Single Receptacles	20A, 125V	1877BK	✓	✓	<input type="checkbox"/> RB303M
		(3) Locking Receptacles	20A, 125V	L520R	✓	-	
		(1) Locking Receptacle	30A, 250V	L630R	✓	-	
		(1) Locking Inlet	50A, 125/250V	CS6375RB	-	-	
		(1) Locking Outlet	50A, 125/250V	CS6369RB	-	-	
50	120/240 (Max.)	(7) WR Duplex Receptacles	20A, 125V	WRBR20BK	✓	✓	<input type="checkbox"/> RB3001M
		(1) Locking Inlet	50A, 125/250V	CS6375RB	-	-	
		(1) Locking Outlet	50A, 125/250V	CS6369RB	-	-	
50	120/240 (Max.)	(7) Locking Receptacles	20A, 125V	L520R	✓	✓	<input type="checkbox"/> RB3021M
		(1) Locking Inlet	50A, 125/250V	CS6375RB	-	-	
		(1) Locking Outlet	50A, 125/250V	CS6369RB	-	-	

Automatic GFCI reset configurations are available. When ordering automatic RhinoBox replace “M” in Catalog No. with “A”. Example: RB300A = Automatic; RB300M = Manual.

NEMA 1 configurations are available. Replace “3” in Catalog No. with “2” for NEMA 1 enclosure. Example: RB300M = NEMA3R; RB200A = NEMA1.

TESTING & CODE COMPLIANCE

- cETLus listed for outdoor use - NEMA 3R products.
- cETLus listed for indoor use - NEMA 1 products.
- Complies with NEC Articles 525 & 590 & OSHA Reg. 29CFR, Part 1926, Subpart K, 1926.404, GFCI requirements.
- Conforms to UL 1640 and CSA C22.2, No. 14

MATERIAL CHARACTERISTICS

- Enclosure: Cold rolled 18 gauge steel.
- Legs: cold rolled 10 gauge steel.

Temporary Power Center Specification & Performance Data

Project Name:	Prepared By:
Project Number:	Date:
Catalog Number:	Type:



Temporary Power Centers with GFCI Protection

50A
120/240 VAC

Application

General maintenance and repair work in industrial facilities; temporary power distribution at construction sites, ship building facilities, expositions, theater, outdoor entertainment, film making, and any other location where temporary power distribution is needed.

Catalog No.	NEMA1 Enclosures RB200M, RB201M, RB202M, RB203M, RB2001M	NEMA3R Enclosures RB300M, RB301M, RB302M, RB303M, RB3001M, RB3021M
Input	50A, 120/240VAC, 60Hz, 3-pole, 4-wire grounding	50A, 120/240VAC, 60Hz, 3-pole, 4-wire grounding
Enclosure Type	NEMA 1	NEMA 3R
GFCI Protection for 20A Receptacles	Yes	Yes
Overload Protection	Yes	Yes
Testing & Code Compliance	cETLus listed for indoor use. Complies with NEC Articles 525 & 590. Complies with OSHA Reg. 29CFR, Part 1926, Subpart K, 1926.404, GFCI requirements. Conforms to UL 1640 and CSA C22.2, No. 14.	cETLus listed for outdoor use. Complies with NEC Articles 525 & 590. Complies with OSHA Reg. 29CFR, Part 1926, Subpart K, 1926.404, GFCI requirements. Conforms to UL 1640 and CSA C22.2, No. 14.
Materials:		
Enclosure	Cold Rolled 18 Gauge Steel	Cold Rolled 18 Gauge Steel
Legs	Cold Rolled 10 Gauge Steel	Cold Rolled 10 Gauge Steel

Automatic GFCI reset configurations are available. When ordering automatic RhinoBox replace "M" in Catalog No. with "A".
Example: RB300A = Automatic; RB300M = Manual.

NEMA 1 configurations are available. Replace "3" in Catalog No. with "2" for **NEMA 1** enclosure.
Example: RB300M = NEMA3R; RB200A = NEMA1.